## Cloth Tape No. 600



#### Strong adhesive strength. Long seller for heavy packaging and packaging for exporting.

A self-adhesive with superior adhesive and holding strength is used on the cloth base. This tape was first used for heavy items and exporting, but it can also be used for the protection of machines because of its thickness.

Usage

- Sealing and packaging cardboard boxes, plastic cases, oil cans, etc.
- Protecting the surfaces of machines and instruments from rust, humidity, and scratches.
- Wrapping and packaging for export

Performance				
Test items	Unit	No. 600 0.310 0.200 4.40 (449) 32 2.20 (225) 0.0 60.0 (6.12)		
Thickness of tape	mm			
Thickness of base material	mm			
Adhesive strength	N/10mm (g/10mm)			
Tack	Ball No.			
Unwinding force	N/10mm (g/10mm)			
Holding power	mm			
Tensile strength	N/10mm (Kg/10mm)			
Elongation	%			

<sup>\*</sup> The figures in the table above are measurements and are not guaranteed values.

Size W (mm)× L (m)	Unit packaging (rolls)	One package (rolls)
25×25	1	60
38×25	1	36
50×25	1	30
60×25	1	30
75×25	1	24
100×25	1	18

* Please feel free to contact us about other size	s.
---	----

Base color
Ocher

Colored
Yellow, green, blue,
red, white, silver,
and black

\*50X25 is the standard size of color tape.

# Heavy packaging Color tape available by hand Non-slip Writable Stackable

### Cloth Tape No. 600V



### More affordable new cloth tape in response to customers' requests

This tape is highly flexible and can be easily torn by hand, making it a tape suitable for many work purposes. To meet the needs of different usages, it is available in many specifications. It can be used from light type to heavy type packaging.

Usage

- Sealing and packaging cardboard boxes, plastic cases, oil cans, etc.
- Heavy packaging requiring adhesive strength
- Delivery
- Packaging for moving

Performance				
Test items	Unit	No. 600V		
Thickness of tape	mm	0.220		
Thickness of base material	mm	0.140		
Adhesive strength	N/10mm (g/10mm)	3.80 (388)		
Tack	Ball No.	32		
Unwinding force	N/10mm (g/10mm)	2.1 (214)		
Holding power	mm	0.1		
Tensile strength	N/10mm (Kg/10mm)	44.0 (4.49)		
Elongation	%	9.0		

<sup>\*</sup> The figures in the table above are measurements and are not guaranteed values.

Size W (mm)× L (m)	Unit packaging (rolls)	One package (rolls)
25×25	1	60
38×25	1	36
50×25	1	30
60×25	1	30
75×25	1	24
100×25	1	18

Base color
Cardboard Color

Heavy packaging	Tear-able by hand	Non-slip	Writable	Stackable	Bundling
	Low				