Kraft Tape No. 500



Excellent holding power and stable quality. Light unwinding force enables excellent workability.

The most frequently used, general purpose tape for packaging cardboard boxes.

A special resin treatment makes it highly moisture-proof and gives it excellent durability against high and low temperatures.

Usage

 Sealing cardboard boxes (medium and light weight)

Performance				
Test items	Unit	No. 500		
Thickness of tape	mm	0.140		
Thickness of base material	mm	0.110		
Adhesive strength	N/10mm (g/10mm)	3.3 (337)		
Tack	Ball No.	12		
Unwinding force	N/10mm (g/10mm)	0.60 (61.2)		
Holding power	mm O			
Tensile strength	N/10mm (Kg/10mm) 60 (6.1			
Elongation	%	8.0		

^{*} The figures in the table above are measurements and are not guaranteed values.

Specifications			
Size W (mm)× L (m)	Unit packaging (rolls)	One package (rolls)	
25×50	10	100	
38×50	6	60	
50×50	5	50	
60×50	4	40	
75×50	3	30	
38×500	_	6	
50×500	_	5	
60×500	_	4	

Base color
Color of cardboard box

Colored
Yellow, green, blue, red and white

- * Color tape in sizes other than 38×50 , 50×50 , 38×500 and 50×500 will be custom-made.
- * Black, light blue, brown, pink, purple and light green are available as semi-standard colors.
- Semi-standard color tape will be custom-made.
- * Please feel free to contact us about other sizes.

Medium and light packaging	Printable	Color tape available	Longer tape available	Special cutter	Quiet
	Environment	Protection from static electricity			

White Kraft Tape



White-color kraft tape

While maintaining the same qualities as those of conventional kraft tape, this white tape will not spoil stylishly designed packages.

This tape is ideal, for instance, for food packages with clean images or cosmetics' packages with a sophisticated feeling.

Usage

- Stylish packages such as cosmetics' packages
- Decoration

Performance			
Test items	Unit	No. 500W	
Thickness of tape	mm	0.140	
Thickness of base material	mm	0.110	
Adhesive strength	N/10mm (g/10mm)	3.3 (337)	
Tack	Ball No.	12	
Unwinding force	N/10mm (g/10mm)	0.60 (61.2)	
Holding power	mm	0	
Tensile strength	N/10mm (Kg/10mm)	60 (6.12)	
Elongation	%	8.0	
Weathering resistance	_	0	
Discoloration resistance	_	0	

* The figures in the table above are measurements and are not guaranteed values.

Specifications			
Size W (mm)× L (m)	Unit packaging (rolls)	One package (rolls)	
25×50	10	100	
38×50	6	60	
50×50	5	50	
60×50	4	40	
75×50	3	30	
38×500	_	6	
50×500	_	5	

* Please feel free to contact us about other sizes.

Medium and light packaging	Printable	Longer tape available	Special cutter	Quiet	Environment
	Protection from static electricity				

White